This leaf issued with A.L. No. 2 October, 1945

AIRCRAFT: SPITFIRE F. Mk. 22

TYPE:

FIGHTER

ENGINE:

GRIFFON 61

Power (Max.)

M: 2,050 b.h.p. at 8,000 ft.

S: 1,780 b.h.p. at 21,000 ft.

DIMENSIONS:

Span

37.1 ft.

Wing area 244 Height

Length 32.7 ft. 13.5 ft.

CREW:

ONE

ARMAMENT **GUNS**

Calibre	No.	Positions	Rds./gun	Remarks
20 mm.	4	Wings, firing forward	150 175	Outboard Inboard

MAXIMUM ALTERNATIVE BOMB LOADS

Under tuselage (lb.)	Wings (lb.)	Total (lb.)
1 × 500	2 × 250 (Late aircraft only)	1,000

WEIGHTS

Maximum 9,200 lb.

8,500 lb. Mean

Light

7,900 lb.

6,900 lb. Tare

(No fuel, oil, bombs, or ammunition)

PERFORMANCE

Take-off over 50 ft. (Max. weight)

625 yds.

Landing over 50 ft. (Light weight)

830 yds.

Service ceiling

(Mean weight) 43,500 ft.

(Max. weight) 43,000 ft.

Maximum speed (Mean weight) M:

420 m.p.h. at 12,000 ft.

S:

454 m.p.h. at 26,000 ft.

Cruising speed (Mean weight) at

20,000 ft.

Most economical

284 m.p.h.

At max. weak mixture power

385 m.p.h.

Time to 20,000 ft. (Max. weight) 8 min.

RANGE (At most economical speed)

With max. Permanent Auxiliary tanks full bomb load tanks full Remarks Fuel carried (gall.) 120 210 Fuel allowance (gall.) 27 29 Bombs (lb.) Range (miles) 490 880